



A. Cosco® Commercial Step Stool

Large 14½w x 12¼d top platform step. Steps have nonskid treads. Folds for easy storage. Durable, tubular steel frame forms handrail and knee brace. WARNING: Metal ladders conduct electricity. Do not use where contact may be made with live electrical circuits. Opti-Bond™ powder-coated finish. Steel frame. 300-lb. capacity. 20½-in. wide.

No.	Steps	Size	Working Height	Each
CSC 11829GGB NEW	2	24¾d x 39½h	21-in.	
CSC 11839GGO NEW	3	32¾d x 52½h	31½-in.	

B. Cosco® Max™ Work Platform

Lightweight, yet durable steel work platform has three heavy-duty polypropylene resin steps with slip-resistant treads and a large 14¾w x 12d top platform step. Handy molded utility tray holds tools, paint cans and wallpaper rolls. Extended hand-grip handle with tool holder. With non-marring, skid-resistant feet to provide stability and protect floor surfaces. Easy one-handed fold and lock release. Select a ladder of the proper duty rating to support the combined weight of the user and the materials. Black steel. 3 steps. 225-lb. weight capacity. 22w x 31d x 55h.

CSC 11880PBLW1 NEW	Each
---------------------------	------



C. Aluminum Euro Platform Ladder

Locking platform provides large standing area. Top rail for safety and convenience. Deeply serrated extruded aluminum steps for security. Slip-resistant foot caps. ANSI Type III, Household, 200-lb. duty rating. 18¾w x 31 spread x 72h. Shpg. wt. 9-lbs.

DAV L2346-03BX	Each
----------------	------

FS1500 Series Fiberglass Step Ladder

Extra heavy-duty, nonconductive industrial stepladder. Equipped with slip-resistant footing and wide back braces. Molded top with handyman's tray and tool slots, along with a convenient magnet for securing small steel tools. Durable and designed for everyday use. Red.

No.	Description	Each
D. DAV FS1502	2-ft.	
E. DAV FS1504	4-ft.	
F. DAV FS1506	6-ft.	

G. Six-Foot Fiberglass Commercial Stepladder

Channeled nonconductive fiberglass rails for strength and corrosion resistance. Deeply serrated U-channel 3-in. steps. Angle bracing strengthens and stabilizes top step, bottom step and rear brace. Yellow molded plastic top holds quart paint can and has slots for small hand tools. Pinch-resistant, heavy-gauge outside side locks. ANSI Type II, Commercial, 225-lb. duty rating. 22¼w x 43½ spread x 72h. Shpg. wt. 16-lbs.


◆DAV 592-06BX	Each
---------------	------



LADDER SAFETY

Ladders, when used properly, can make common large-scale jobs so much easier. And if used properly and according to safety guidelines, it can give many years of trouble-free service. However, if proper cautions are not taken, a ladder can create a potentially hazardous situation. Fortunately, many injuries can be avoided by following the following safety tips:

- Check the ladder for any loose screws, hinges or rungs.
- Clean off any mud, grease, oil, snow or other slippery liquids
- Keep your shoes clean; leather soles should never be used.
- Make sure to check if your ladder is damaged, broken or bent.



15-LG-AN

FACILITY MAINTENANCE

Prices are subject to change.