



A. Original Protectant

Protects vinyl, rubber and plastic from fading and cracking caused by UV, ozone, oxidation and extreme temperatures. Water-based formula.

No.	Size	Qty./Case	Case
ARM 10228	28-oz. Trigger Sprayer	6	
◆ARM 10326	32-oz. Trigger Sprayer	6	
ARM 10710	Gallon Bottle	4	



A



B. Brake Parts Cleaner II

Non-chlorinated fast-dry formula easily removes brake fluid, grease, oily dirt and contaminants from lining, pads and drums, cylinders and springs, without disassembling the unit. NSF/USDA Classification P1. Not available for sale in California or LADCO and OTC regions. 20-oz. aerosol can—14-oz. net wt. 12 cans per case.

AMR A734-20	Case
-------------	------

C. ICS Energized Electrical Cleaner

Fast-dry, non-flammable, chlorinated formula rapidly removes dirt, grease, oil and grime from metallic and nonmetallic surfaces. Ideal for use on electric motors (even while running), electronic equipment, ignition systems, typewriters, computers, etc. Safe on most plastics. NSF/USDA Classification K2. 20-oz. aerosol can—20-oz. net wt. 12 cans per case.

AMR A365-20	Case
-------------	------

D. Si-Dry Silicone Lubricant

Ultra fast-drying textile-grade silicone spray provides light lubrication for a wide variety of surfaces in textile plants, including cutting tables, needles, blades, foam/fabric installation and other applications. Intended for use in producing, processing, treating, preparing, transporting or holding food. Medium viscosity formula is colorless, odorless, heat stable and non-staining. Hexane-free and low VOC, it contains no carcinogens or chlorinated solvents and won't deplete the ozone. 16-oz. aerosol can—11-oz. net wt. 12 cans per case.

AMR A329-16	Case
-------------	------

E. Penetrating Lubricant

A non-flammable four-in-one spray loosens, cleans and lubricates frozen nuts, bolts and moving parts. Fortified with PTFE. Also stops and prevents corrosion. NSF/USDA Classification H2. 20-oz. aerosol can—19-oz. net wt. 12 cans per case.

AMR A390-20	Case
-------------	------

F. Red Grease

An extra heavy-duty, non-melt grease specially formulated with extreme pressure and anti-wear additives. Excellent adhesive and cohesive properties. Resists most acids, salt, dirt, steam, corrosion and oxidation. Timken load 65. NSF/USDA Classification H2. 14-oz. tube. 48 tubes per case.

AMR RL726-48	Case
--------------	------



B



C



D



E



F

REASONS TO USE LUBRICANTS

Tips and Tricks for Zep PTFE Multipurpose Lubricant:

- Keeps pliers, shears or other hinged tools working smoothly.
- Lubricates noisy door hinges on facilities or work vehicles.
- Lubricates tracks in sticking windows and makes them easier to open.
- Lubricates and stops squeaks in electric fans.
- Keeps rust from forming on saws, saw blades and other tools.
- Removes residual traces of duct tape.
- Use on metal cables and linkages for lubrication and to protect from rust.



15-LG-AN

CHEMICALS

Prices are subject to change.