MATERIAL SAFETY DATA SHEET
This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND MANUFAC	CTUF	RER'S INFORMATIO	N			
NFPA Rating: Health-2; Flammability-2; Reactivity-0; Special-0  HMIS Rating: Health-2; Flammability-2; Reactivity-0; Personal Protection-B						
anufacturer's Name: AMREP, INC.  DOT Hazard Classification: ORM-D						
, -	Identity (trade name as used on label):					
Marietta, GA 30062	MISTY FURNITURE POLISH					
·	MSDS Number: 134 Revision- 10					
Information Calls: (770)422-2071						
EMERGENCY RESPONSE NUMBER: 1(800)255-3924						
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION						
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES	IFIC			OCUA DEL	400111	0
(Hazardous Components 1% or greater; Carcinogens 0.1% or greater)		CAS Number	SARA III LIST	OSHA PEL	ACGIH TLV (ppm)	Carcinogen Ref. Source **
PETROLEUM DISTILLATES		90E2 44 2		(ppm)		
ISOBUTANE / PROPANE BLEND		8052-41-3	No	100	100	d
ISOBUTANE / PROPANE BLEND		75-28-5	No	800	800	d
		74-98-6	No	1000	1000	d
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS						
Boiling Point: N/A Specific Gravity (H2O=1): Concentrate Only = 0.948						
	Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A					
	Evaporation Rate (BuAc = 1): Slower					
Solubility in Water: Slight Water Reactive: No						
Appearance and Odor: Creamy white spray with lemon fragrance.						
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA						
FLAMMABILITY as per USA FLAME PROJECTION TEST  Auto Ignition Temperature  Flammability Limits in Air by % in Volume:						
(aerosols) NON-FLAMMABLE N/E % LEL: N/E % UEL: N/E						
FLASH POINT AND METHOD USED (non-aerosols): N/A EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide.						
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus.						
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.						
SECTION 4 - REACTIVITY HAZARD DATA						
SECTION 4 - REACTIVITY HAZARD DATA  STABILITY [X] STABLE [] UNSTABLE HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR						
Incompatibility (Mat. to avoid): Strong oxidizers and alkalies.  Conditions to Avoid: Open flame, welding arcs, heat, sparks.						
Hazardous Decomposition Products: CO2, CO, hydrogen chloride.						
SECTION 5 - HEALTH HAZARD DATA						
PRIMARY ROUTES OF ENTRY: [X]INHALATION []INGESTION [X]SKIN ABSORPTION []EYE []NOT HAZARDOUS						
ACUTE EFFECTS:						
Inhalation: Excessive inhalation of vapors can be harmful and may cause headaches, dizziness, asphyxia, anesthetic effects and possible unconsciousness.						
Eye Contact: Mild irritant. Skin Contact: Mild irritant.						
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.						
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) May cause cardiac abnormality, liver abnormalities, kidney and/or						
lung damage.						
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, upper respiratory conditions, liver disease & heart irregularities.						
EMERGENCY FIRST AID PROCEDURES						
Eye Contact: Flush with water for at least 15 minutes. If irritated, seek medical attention.						
Skin Contact: Wash with soap and water. Remove contaminated clothing & launder before re-wearing. If irritated, seek medical attention.						
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.						
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.						
SECTION 6 - CONTROL AND PROTECTIVE MEASURES						
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved bu U.S. Bureau of Mines for organic vapor.						
Protective Gloves: Latex if skin is easily irritated.						
Other Protective Clothing & Equipment: None						
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.						
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE						
Steps To Be Taken If Material Is Spilled Or Released: Absorb spilled liquid with suitable medium. Incinerate or landfill according to local, state or Federal						
regulations. DO NOT FLUSH TO SEWER.						
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.						
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.						
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors.						

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

\*\* Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only