



**The Clorox Company**

1221 Broadway  
Oakland, CA 94612  
Tel. (510) 271-7000

# Material Safety Data Sheet

<b>I Product:</b> GREEN WORKS™ NATURAL ALL PURPOSE CLEANER											
<b>Description:</b> LIQUID WITH LEMON ODOR											
<b>Other Designations</b>	<b>Distributor</b>	<b>Emergency Telephone Nos.</b>									
	Clorox Sales Company 1221 Broadway Oakland, CA 94612	For Medical Emergencies call: 1-800-446-1014 For Transportation Emergencies, call Chemtrec: 1-800-424-9300									
<b>II Health Hazard Data</b>		<b>III Hazardous Ingredients</b>									
<p>Eye irritant. May cause skin irritation. No medical conditions are known to be aggravated by exposure to this product.</p> <p><b>FIRST AID:</b></p> <p><u>EYE CONTACT:</u> Immediately rinse with plenty of water. If irritation persists, call a doctor.</p> <p><u>INGESTION:</u> Drink a glassful of water. Call a doctor or poison control center.</p> <p><u>SKIN CONTACT:</u> Rinse with plenty of water. If irritation persists, call a doctor.</p> <p><u>INHALATION:</u> Move person to fresh air. If breathing problems develop, call a doctor.</p>		<table border="1"> <thead> <tr> <th><u>Ingredient</u></th> <th><u>Concentration</u></th> <th><u>Worker Exposure Limit</u></th> </tr> </thead> <tbody> <tr> <td>Alkyl polyglucoside CAS # 68515-73-1</td> <td>2 - 5%</td> <td>not established</td> </tr> <tr> <td>Ethyl alcohol CAS # 64-17-5</td> <td>1 - 3%</td> <td>1000 ppm - TLV-TWA 1000 ppm - OSHA PEL</td> </tr> </tbody> </table> <p>TLV-TWA = ACGIH Threshold Limit Value - Time Weighted Average OSHA-PEL = OSHA Permissible Exposure Limit - Time Weighted Average None of the materials in this product are on the IARC, OSHA, or NTP carcinogen lists.</p>	<u>Ingredient</u>	<u>Concentration</u>	<u>Worker Exposure Limit</u>	Alkyl polyglucoside CAS # 68515-73-1	2 - 5%	not established	Ethyl alcohol CAS # 64-17-5	1 - 3%	1000 ppm - TLV-TWA 1000 ppm - OSHA PEL
<u>Ingredient</u>	<u>Concentration</u>	<u>Worker Exposure Limit</u>									
Alkyl polyglucoside CAS # 68515-73-1	2 - 5%	not established									
Ethyl alcohol CAS # 64-17-5	1 - 3%	1000 ppm - TLV-TWA 1000 ppm - OSHA PEL									
<b>IV Special Protection and Precautions</b>		<b>V Transportation and Regulatory Data</b>									
<p><u>Hygienic Practices:</u> Wash hands after direct contact. Do not wear product-contaminated clothing for prolonged periods.</p> <p><u>Engineering Controls:</u> Use local exhaust to minimize exposure to product mist.</p> <p><u>Personal Protective Equipment:</u> Wear safety glasses. Wear rubber or neoprene gloves if there is the potential for repeated or prolonged skin contact. In situations where exposure limits may be exceeded, a NIOSH-approved respirator is advised.</p>		<p><u>DOT/IATA/IMDG:</u> Not restricted.</p> <p><u>EPA - SARA Title III/CERCLA:</u> This product is regulated under Sections 311/312. This product contains no chemicals which are regulated under Section 313 or regulated under Section 304/CERCLA.</p>									
<b>VI Spill Procedures/Waste Disposal</b>		<b>VII Reactivity Data</b>									
<p><u>Spill Procedures:</u> Absorb and containerize. Wash residual down to sanitary sewer. Contact the sanitary treatment facility in advance to assure ability to process washed-down material.</p> <p><u>Waste Disposal:</u> Dispose of in accordance with all applicable federal, state, and local regulations.</p>		Stable under normal use and storage conditions.									
<b>VIII Fire and Explosion Data</b>		<b>IX Physical Data</b>									
<p><u>Flash Point:</u> &gt;200°F (closed cup)</p> <p><u>Fire Extinguishing Agents:</u> Dry chemical, carbon dioxide (CO<sub>2</sub>), foam, or water spray.</p>		<p>pH..... ~7.0</p> <p>Specific gravity ..... 1.0</p> <p>Solubility in water ..... Soluble</p>									