GENUINE JOE STAINLESS STEEL CLEANER GJ02114

Version 1.0 Revision Date 04/24/2015 Print Date 06/04/2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : Genuine Joe Stainless Steel

Material number : A00141

Manufacturer or supplier's details

Company : S.P Richards Co.

Address : 6300 Highlands Parkway

Smyrna, GA 30082

Telephone : 1-877-541-2016

Emergency telephone numbers

For SDS Information : 1-877-541-2016

For a Medical Emergency :

For a Transportation : 1-877-541-2016

Emergency

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	clear
Odour	characteristic

GHS Classification

Flammable aerosols : Category 1
Gases under pressure : Liquefied gas
Skin irritation : Category 2
Skin sensitisation : Category 1

GHS Label element

Hazard pictograms :





Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

Precautionary statements : **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after

ıse.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

GENUINE JOE STAINLESS STEEL CLEANER GJ02114

Version 1.0 Revision Date 04/24/2015 Print Date 06/04/2015

P272 Contaminated work clothing should not be allowed out of

the workplace. P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/122 °F.

Disposal:

P501 Dispose of contents/container in accordance with local

regulation.

Potential Health Effects

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical Name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 50 - < 70
Distillates (petroleum), hydrotreated light	64742-47-8	>= 20 - < 30
propane	74-98-6	>= 5 - < 10
butane	106-97-8	>= 5 - < 10
citral	5392-40-5	>= 0.1 - < 1

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

GENUINE JOE STAINLESS STEEL CLEANER GJ02114

Version 1.0 Revision Date 04/24/2015 Print Date 06/04/2015

In case of skin contact : If skin irritation persists, call a physician.

Wash off immediately with plenty of water for at least 15

minutes.

If on clothes, remove clothes.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist. If in eyes, rinse with water for 15 minutes.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical Water spray jet

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

GENUINE JOE STAINLESS STEEL CLEANER GJ02114

Version 1.0 Revision Date 04/24/2015 Print Date 06/04/2015

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Sweep up or vacuum up spillage and collect in suitable

container for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges.

Provide sufficient air exchange and/or exhaust in work rooms.

Open drum carefully as content may be under pressure.

Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Always replace cap after use.

Do not breathe vapours or spray mist.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects. No smoking.

Keep in a dry, cool and well-ventilated place.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA	5 mg/m3	ACGIH

GENUINE JOE STAINLESS STEEL CLEANER GJ02114

Version 1.0 Revision Date 04/24/2015 Print Date 06/04/2015

		(Inhalable fraction)		
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Safety glasses

Ensure that eyewash stations and safety showers are close to

the workstation location.

Skin and body protection : impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a liquefied gas

Colour : clear

Odour : characteristic
Odour Threshold : no data available
pH : no data available
Melting point/freezing point : no data available
Boiling point : no data available

Flash point

not applicable

GENUINE JOE STAINLESS STEEL CLEANER GJ02114

Version 1.0 Revision Date 04/24/2015 Print Date 06/04/2015

Evaporation rate : no data available

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit : no data available

Lower explosion limit : no data available

Vapour pressure : 4,136 hPa (21 °C)

Relative vapour density : no data available

Density : 0.856 g/cm3

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: no data available

Auto-ignition temperature : not determined

Thermal decomposition : no data available

Viscosity

Viscosity, kinematic : no data available

Heat of combustion : 46.27 kJ/g

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Extremes of temperature and direct sunlight.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

: Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Components:

Distillates (petroleum), hydrotreated heavy naphthenic: Acute oral toxicity : LD50 rat: > 5,000 mg/kg

GENUINE JOE STAINLESS STEEL CLEANER GJ02114

Version 1.0 Revision Date 04/24/2015 Print Date 06/04/2015

Acute inhalation toxicity : LC50 rat: > 5 mg/l

Exposure time: 4 h

Acute dermal toxicity : LD50 rabbit: > 5,000 mg/kg

Distillates (petroleum), hydrotreated light:

Acute oral toxicity : LD50 rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 rat: > 4.6 mg/l

Exposure time: 6 h

Acute dermal toxicity : LD50 rat: > 2,000 mg/kg

propane:

Acute inhalation toxicity : LC50 mouse: 1,237 mg/l

Exposure time: 2 h

LC50 rat: 658 mg/l Exposure time: 4 h

LC50 rat: 1,355 mg/l

butane:

Acute inhalation toxicity : LC50 mouse: 1,237 mg/l

Exposure time: 2 h

LC50 rat: 1,355 mg/l

Skin corrosion/irritation

Product:

Remarks: Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Respiratory or skin sensitisation

Product:

Remarks: Causes sensitisation.

Germ cell mutagenicity

no data available

Carcinogenicity

no data available

Reproductive toxicity

no data available

GENUINE JOE STAINLESS STEEL CLEANER GJ02114

Version 1.0 Revision Date 04/24/2015 Print Date 06/04/2015

Distillates (petroleum), hydrotreated heavy naphthenic:

Distillates (petroleum), hydrotreated light:

propane:

butane: citral:

STOT - single exposure

no data available

STOT - repeated exposure

no data available

Aspiration toxicity

no data available

Further information

Product:

Remarks: no data available

Components:

Distillates (petroleum), hydrotreated light:

Remarks: no data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

no data available

Persistence and degradability

no data available

Bioaccumulative potential

Product:

Partition coefficient: n-

: Remarks: no data available

octanol/water Components:

butane:

Partition coefficient: n- : Pow: 2.89

octanol/water

citral:

Partition coefficient: n- : Pow: 2.76

octanol/water

Mobility in soil

no data available

Other adverse effects

no data available

Product:

GENUINE JOE STAINLESS STEEL CLEANER GJ02114

Version 1.0 Revision Date 04/24/2015 Print Date 06/04/2015

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to

aquatic life with long lasting effects.

Components:

Distillates (petroleum), hydrotreated light :

Additional ecological

information

: no data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):

UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, 2.1, - Limited quantity

GENUINE JOE STAINLESS STEEL CLEANER GJ02114

Version 1.0 Revision Date 04/24/2015 Print Date 06/04/2015

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Sudden Release of Pressure Hazard

Acute Health Hazard

Fire Hazard

SARA 302 : SARA 302: No chemicals in this material are subject to the

reporting requirements of SARA Title III, Section 302.

SARA 313 : SARA 313: This material does not contain any chemical

components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA

Title III, Section 313.

California Prop 65 This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

The components of this product are reported in the following inventories:

TSCA On TSCA Inventory

DSL This product contains one or several components that are not on the

Canadian DSL nor NDSL.

AICS
Not in compliance with the inventory
NZIOC
Not in compliance with the inventory
PICCS
Not in compliance with the inventory
IECSC
Not in compliance with the inventory

Inventory Acronym and Validity Area Legend:

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

GENUINE JOE STAINLESS STEEL CLEANER GJ02114

Version 1.0 Revision Date 04/24/2015 Print Date 06/04/2015

Further information

NFPA:

Flammability

Special hazard.

HMIS III:

HEALTH	3
FLAMMABILITY	4
PHYSICAL HAZARD	2

0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic

OSHA GHS Label Information:

Hazard pictograms







Signal word : **Danger:** Hazard statements : Extreme

: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. May cause an allergic skin reaction.

Precautionary statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/ furme/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves. Response: IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F

Disposal: Dispose of contents/container in accordance with local regulation.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

1047595