Conforms to USDOL OSHA 29CFR 1910.1200 HAZCOM

SAFETY DATA SHEET

Air Wick Freshmatic Ultra - Pure Tropical Flowers



1. Product and company identification

Product name	: Air Wick Freshmatic Ultra - Pure Tropical Flowers
Distributed by	: Reckitt Benckiser LLC. Morris Corporate Center IV 399 Interpace Parkway (P.O. Box 225) Parsippany, New Jersey 07054-0225 +1 973 404 2600
Emergency telephone number (Medical)	: 1-800-338-6167
Emergency telephone number (Transport)	: 1-800-424-9300 (U.S. & Canada) CHEMTREC Outside U.S. and Canada (North America), call Chemtrec:703-527-3887
Website:	: http://www.rbnainfo.com

Product use : Air care, instant action (aerosol sprays)

This SDS is designed for workplace employees, emergency personnel and for other conditions and situations where there is greater potential for large-scale or prolonged exposure, in accordance with the requirements of USDOL Occupational Safety and Health Administration.

This SDS is not applicable for consumer use of our products. For consumer use, all precautionary and first aid language is provided on the product label in accordance with the applicable government regulations, and shown in Section 15 of this SDS.

SDS #	: D8282584
Formulation #:	: #8276558_1

Relevant identified uses of the substance or mixture and uses advised against Not applicable.

2. Haz	Hazards identification					
	ation of the e or mixture		AEROSOLS - Cate ER PRESSURE - Lie			
	<u>I elements</u> pictograms		$\langle \cdot \rangle$			
Signal w	vord	: Danger				
Hazard	statements		mmable aerosol. under pressure; ma	y explode if heated.		
Precaut	ionary statements					
Code #	: FF8276558_1	SDS #	: D8282584	Date of issue	: 19/09/2016.	1/12

2. Hazards identification

General	Read label before use. Keep out of reach of children. If medical advice is needed	J,
	have product container or label at hand.	
Prevention	Keep away from heat, hot surfaces, sparks, open flames and other ignition source smoking. Pressurized container: Do not pierce or burn, even after use. Do not sp an open flame or other ignition source.	
Response	Not applicable.	
Storage	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. S a well-ventilated place.	tore in
Disposal	Not applicable.	
Supplemental label elements	None known.	
Hazards not otherwise classified	None known.	

3. Composition/information on ingredients

: Mixture

Ingredient name	%	CAS number
Distillates (petroleum), hydrotreated light	> 60	64742-47-8

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

Description of necessary fir	<u>st aid measures</u>
Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	 Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Code # : FF8276558 1	SDS # : D8282584 Date of issue : 19/09/2016. 2/12

4. First aid measures

Most important symptoms/effects, acute and delayed Potential acute health effects Eye contact : No known significant effects or critical hazards. Inhalation : Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure. Skin contact : No known significant effects or critical hazards. Ingestion : No known significant effects or critical hazards. **Over-exposure signs/symptoms** Eye contact : Adverse symptoms may include the following: irritation redness Inhalation : Adverse symptoms may include the following: respiratory tract irritation coughing **Skin contact** : No specific data. Ingestion : No specific data. Indication of immediate medical attention and special treatment needed, if necessary Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed

Notes to physician	The exposed person may need to be kept under medical surveillance for 48 hours.	
Specific treatments	No specific treatment.	
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It n be dangerous to the person providing aid to give mouth-to-mouth resuscitation.	nay

See toxicological information (Section 11)

5. Fire-fighting measures

Extinguishing media		
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.	
Unsuitable extinguishing media	: None known.	
Specific hazards arising from the chemical	: Extremely flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. Runoff to sewer may create fire or explosion hazard. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.	
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds carbonyl halides	
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.	
Code # : FF8276558_1	SDS # : D8282584 Date of issue : 19/09/2016. 3/12	

5. Fire-fighting measures

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

a la sub la sub la sub la sub sub s

6. Accidental release measures

Personal precautions, pr	tective equipment and emergency procedures
For non omorgonov	No action shall be taken involving any personal r

. . .

Por non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
Methods and materials for c	entainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

7. Handling and storage

Precautions for safe handling

Protective measures
 Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.

7. Handling and storage

Conditions for safe storage, including any incompatibilities incompatibilities

8. Exposure controls/personal protection

Control

Occupational exposure limits

Ingredient name Distillates (petroleum), hydro	otreated light	Exposure limits ACGIH TLV (United States, 4/2014). Absorbed through skin. TWA: 200 mg/m ³ , (as total hydrocarbon vapor) 8 hours.		
Appropriate engineering controls	or mist, use process enclosures to keep worker exposure to airb limits. The engineering controls	Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.		
Environmental exposure controls	they comply with the requirement cases, fume scrubbers, filters o	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.		
Individual protection measu	ires			
Hygiene measures	eating, smoking and using the la Appropriate techniques should l	e thoroughly after handling chemical products, before avatory and at the end of the working period. be used to remove potentially contaminated clothing. fore reusing. Ensure that eyewash stations and safety tation location.		
Eye/face protection	assessment indicates this is ne gases or dusts. If contact is po	assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-		
Skin protection				
Hand protection	worn at all times when handling necessary. Considering the par during use that the gloves are s noted that the time to breakthro	gloves complying with an approved standard should be chemical products if a risk assessment indicates this is rameters specified by the glove manufacturer, check till retaining their protective properties. It should be ugh for any glove material may be different for different se of mixtures, consisting of several substances, the nnot be accurately estimated.		
Body protection	performed and the risks involve handling this product. When the static protective clothing. For the	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear antistatic protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.		
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.			

8. Exposure controls/personal protection

```
Respiratory protection
```

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

9. Physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid. [Aerosol.]
Color	: Not available.
Odor	: Characteristic.
Odor threshold	: Not available.
рН	: Not available.
Melting point	: Not available.
Boiling point	: <34°C (<93.2°F)
Flash point	: Closed cup: <0°C (<32°F)
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Not available.
Vapor pressure	: Not available.
Vapor density	: Not available.
Relative density	: 0.66 to 0.70
Solubility	: Not available.
Partition coefficient: n- octanol/water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Not available.
Aerosol product	
Type of aerosol	: Spray
Heat of combustion	: 40.52 kJ/g

10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame).
Incompatible materials	: Do not mix with household chemicals.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

Information on toxicological effects

Acute toxicity

Not available.

Irritation/Corrosion

Not available.

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Name	Result
Distillates (petroleum), hydrotreated light	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure	: Not available.
Potential acute health effec	<u>ts</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
<u>Symptoms related to the pr</u> Eye contact	 Adverse symptoms may include the following: irritation redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: No specific data.
Ingestion	: No specific data.

11. Toxicological information

Delayed and immediate effects and also chronic effects from short and long term exposure

<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
<u>Long term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	<u>ects</u>
Not available.	
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates Not available.

12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Distillates (petroleum), hydrotreated light	Acute LC50 2200 µg/l Fresh water	Fish - Lepomis macrochirus	4 days

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

<u>Mobility in soil</u>	
Soil/water partition	:
coefficient (Koc)	

Not available.

Other adverse effects : No known significant effects or critical hazards.

Code #	5	FF8276558_	1
--------	---	------------	---

SDS #

: D8282584

13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

14. Transport information

Regulatory	UN number	Proper shipping	Classes	PG*	Label	Additional
information	on number	name	0103363		Laber	information
DOT Classification	UN1950	Aerosols	2.1	-	\bigcirc	Limited quantity
TDG Classification	UN1950	AEROSOLS	2.1	-	\bigcirc	Limited quantity
Mexico Classification	UN1950	AEROSOLES	2.1	-	\bigcirc	Limited quantity
IMDG Class	UN1950	AEROSOLS	2.1	-	\bigcirc	Limited quantity
IATA-DGR Class	UN1950	Aerosols, flammable	2.1	-		See DG List

PG* : Packing group

PG*: Packing group						
15. Regulatory information						
U.S. Federal regulations	anisaldehyde	; 3-p-cumenyl-2-met	nzyl)propionaldehyde; hylpropionaldehyde; 4 Ildehyde; benzaldehyd	-(4-methyl-3-penter	yl)cyclohex-3	
	TSCA 8(a) C	DR Exempt/Partial	exemption: Not deter	mined		
	United State	United States inventory (TSCA 8b): Not determined.				
	Clean Air Ao 1-difluoroeth	· / •	ed flammable substa	inces : propane; but	ane; 1,	
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	: Not listed					
Clean Air Act Section 602 Class I Substances	: Not listed					
Code # : FF8276558 1	SDS #	: D8282584	Date of issue	: 19/09/2016.	9/12	

15. Regulatory information


· · · · · · · · · · · · · · · · · · ·	
Clean Air Act Section 602 Class II Substances	: Not listed
DEA List I Chemicals (Precursor Chemicals)	: Not listed
DEA List II Chemicals (Essential Chemicals)	: Not listed
SARA 302/304	
Composition/information	on ingredients
No products were found.	
SARA 304 RQ	: Not applicable.
<u>SARA 311/312</u>	
Classification	: Fire hazard Sudden release of pressure
Composition/information	on ingredients
No products were found.	
State regulations	
Massachusetts	: The following components are listed: PROPANE; BUTANE; DIFLUOROETHANE
New York	: None of the components are listed.
New Jersey	 The following components are listed: PROPANE; BUTANE; 1,1-DIFLUOROETHANE; ETHANE, 1,1-DIFLUORO-
Pennsylvania	: The following components are listed: PROPANE; BUTANE
<u>Canada</u>	
WHMIS (Canada)	: Class B-2: Flammable liquid Class B-5: Flammable aerosol.
<u>Canadian lists</u>	
Canadian NPRI	: The following components are listed: Hydrotreated light distillate; Propane; Butane (all isomers); Volatile organic compounds
CEPA Toxic substances	: The following components are listed: Volatile organic compounds
Canada inventory	: Not determined.
Label elements	
Hazard statements	
	Flammable
Recommendations	: People suffering from perfume sensitivity should be cautious when using this product. Air Fresheners do not replace good hygiene practices.

÷

D8282584

16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



NFPA (30B) aerosol Flammability Level 3

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Key to abbreviations	 ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations
Date of issue	: 19/09/2016.
Date of previous issue	: 21/07/2015.
Version	: 1
Prepared by	: Reckitt Benckiser LLC. Product Safety Department 1 Philips Parkway Montvale, New Jersey 07646-1810 USA. FAX: 201-476-7770

16. Other information

Revision comments

: Update as per OSHA GHS.

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.



RB is a member of the CSPA Product Care Product Stewardship Program.