



Maintenance Solutions

Rebound

High Speed Buffing Creme

For Use On:

Vinyl Tile
Vinyl Asbestos
Asphalt Tile

Linoleum
Rubber Tile
Terrazzo

Sealed Wood
Quarry Tile
Marble



DESCRIPTION

The ideal companion product for use with any high speed maintenance program. This cleaning compound is designed to protect and beautify any resilient tile, sealed wood, ceramic, terrazzo, quarry tile, or other hard surface flooring while reducing time and labor.

DIRECTIONS

Sweep or dust mop the floor to remove dirt and grime that may scratch the finish during the buffing operation. Place a burnishing pad under a 1000 rpm or higher floor machine. Apply a 3-4 inch strip of cream in front of the machine and spread with the pad over a 800 to 1000 square foot area. Once the entire floor is done, sweep or dust the floor again.

PRODUCT SPECIFICATIONS

Color:	Milky emulsion	Black Mark Resistance:	Excellent
Odor:	Citrus	Sediment:	0.01% by volume, max.
Base:	Proprietary polymers	Buffability:	Excellent
pH:	9.0 -9.5	Biodegradability:	Completely
Viscosity:	Viscous gel	Storage/Stability:	2 years
Slip Resistance:	Will not increase slip	Weight per Gallon:	8.43 lbs./gal.
Abrasives:	None	Freeze/Thaw Stability:	Keep from freezing
Flash Point:	None (waterbased)		

SECTION 1-PRODUCT IDENTIFICATION AND SUPPLIER INFORMATION

Manufacturer's Name: Misco Products Corporation	Product Name: Rebound
Manufacturer's Address: 1048 Stinson Drive Reading, PA 19605	Generic Name: Hi-Speed Buffing Creme
Manufacturer's Phone #: (610) 926-4106	Chemical Family: Acrylic Polymer Blend
	Formula: Proprietary

SECTION 2-INGREDIENT INFORMATION

CHEMICAL NAME	CAS NO.	WT. %	PEL	TWA-TLV	STEL-TLV
Water	7732-18-5	to 100			
Acrylic Copolymer Dispersion	Proprietary	5 to 10			
Polyethylene Copolymers	Proprietary	5 to 10			
Polyethylene Glycols	Proprietary	5 to 10			
Citrus Terpenes	5989-27-5	0 to 5			
Nonionic Surfactant	9016-45-9	0 to 5			

SECTION 3-PHYSICAL DATA

Boiling Point (°F): 212 F.	Specific Gravity: 1.012
Vapor Pressure: 20mm Hg @ 68 F.	Vapor Density (Air=1): >1
% Volatile: 90+	pH: 9.0-9.5
Solubility in Water: Complete	Evaporation Rate (Water=1): <1
Physical Description: Thick white creamy liquid with pleasant odor.	

SECTION 4-FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): N/A	Lower Explosion Limit: N/A
Upper Explosion Limit: N/A	
Extinguishing Media: N/A	
Special Firefighting Procedures: Non Flammable	
Unusual Fire and Explosion Hazards: N/A	

SECTION 5-REACTIVITY DATA

Stability: Stable	Hazardous Polymerization: None
Hazards Decomposition Products: Will not occur.	Incompatibility (Materials to Avoid): None

SECTION 6-STORAGE AND HANDLING INFORMATION

Keep out of reach of children. For use by trained personnel only. Keep unauthorized personnel away when applying to floor. Keep container closed during storage. For institutional and industrial use only. Avoid contact with eyes, skin and clothing. Avoid breathing of vapors. Use in well-ventilated area.

SECTION 7-HEALTH HAZARDS AND FIRST AID

Effects of Overexposure:
Skin: Prolonged or repeated contact may cause dermatitis.
Eyes: Eye irritant. May cause redness or swelling.
Inhalation: N/A
Ingestion: May be irritating to the mouth, throat, and gastrointestinal system. Vomiting and diarrhea expected with large doses.

Respiratory Protection: No special requirements.
Ventilation Requirements: Provide local exhaust to keep TLV of Section 2 ingredients below acceptable limit.
Protective Gloves: N/A
Eye Protection: N/A
Other Protective Equipment: N/A

First Aid Procedures:

Skin: Flush with water. Seek medical attention if irritation persists.
Eyes: Flush with large quantities of water, holding eyelids open. Seek medical attention.
Inhalation: N/A
Ingestion: Dilute with 2 glasses of water. Seek medical attention if symptoms persist.

SECTION 9-SPILL OR LEAK PROCEDURES

Steps to be taken in Case Material is Released or Spilled: Floors will become slippery. Avoid walking in product. Keep unessential personnel away. Mop up or otherwise absorb and hold disposal. Avoid discharge to sewer or open waterways.
Waste Disposal Method: Any method in accordance with local, state and federal laws. Best method is to recycle or reuse for intended purpose. Consult local authorities for disposal in public sewer. Do not dispose of into storm drain, stream, river or to ground. Rinse container thoroughly before discarding in trash.

SECTION 10-REGULATORY INFORMATION

SARA Title III - Section 311/312 -Hazard Categories:	Shipping Information:
No - Fire Hazard	FOR CONTAINERS > 1 Gallon : Cleaning Compound
No - Sudden Release of Pressure Hazard	
No - Reactivity Hazard	FOR 1 GALLON CONTAINERS : Cleaning Compound
Yes - Immediate (acute) Health Hazard	
No - Delayed (chronic) Health Hazard	FOR CONTAINERS < 1 GALLON : Cleaning Compound

HMIS Hazardous Materials Identification System

Health	1
Flammability	0
Reactivity	0
Personal Protection	A

FOR EMERGENCY MEDICAL OR TRANSPORT INFORMATION: CHEM-TEL, Inc. @ 800-255-3924 (24 hours, 7 days per week)

This product contains the following toxic chemical(s) subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

CAS#	Chemical Name	Percent by Weight
	None	

This product contains the following chemical(s) which have been established to be either a carcinogen or suspected carcinogen.

CAS#	Chemical Name	Percent by Weight
	None	

SECTION 11-OTHER INFORMATION

This company cannot anticipate all conditions of handling and use of this product. Therefore, this company accepts no responsibility for results obtained by the application of this information, or the safety and suitability of our products either alone or in combination with other products. It is the responsibility of the user to provide a safe workplace, using the health and safety information contained herein as a guide. This company will accept no liability for damages or loss incurred from the improper handling and use of this product